



C Filters

Ph: (03) 9543 3339 Fax: (03) 9543 3379



Email us your enquiry. info@cfilters.com

Cardboard Disposable Filters.

Pleated Panel Cartridge Filters.

Applications.	Coarse particle filtration.
Type.	Pleated panel filter.
Frame and Grids.	Water resistant cardboard.
EN 779 Class.	G4
Average arrestance.	92% (ASHRAE 52.1 -1992)
MERV	MERV 9 (ASHRAE 52.2 -1999)
DIN 53438 Flammability	F1
UL 900 Standards.	CLASS 2
Final pressure drop.	(recommended) 200Pa - (maximum) 250Pa
Max. Air flow rate.	125% of nominal air flow rate
Max. Operating temperature.	70°C
Max. Relative humidity.	100%
Filter media.	Synthetic fibre.

Type	Class	Arrestance	Dimensions			Filtering surface (m ²)	Rated air flow (m ³ /h)	Initial pressure drop (Pa)
			Length (mm)	Height (mm)	Depth (mm)			
CFCAR2424	G4	90-94%	595	595	45	1.10	3000	80
CFCAR2020	G4	90-94%	495	495	45	0.75	2000	80
CFCAR2024	G4	90-94%	595	495	45	0.90	2500	80
CFCAR2025	G4	90-94%	622	495	45	1.12	3000	80
CFCAR1620	G4	90-94%	495	395	45	0.75	1500	80
CFCAR1625	G4	90-94%	595	395	45	0.75	2000	80
CFCAR1224	G4	90-94%	595	295	45	0.55	1500	80
CFCAR24241	G4	90-94%	595	595	95	2.00	3500	100
CFCAR20241	G4	90-94%	595	495	95	1.60	3000	100
CFCAR20251	G4	90-94%	622	495	95	2.00	3000	100
CFCAR16241	G4	90-94%	595	395	95	1.30	2300	100
CFCAR12241	G4	90-94%	595	295	95	1.00	1750	100
CFCAR20201	G4	90-94%	495	495	95	1.30	2300	100
CFCAR16201	G4	90-94%	495	395	95	1.00	1750	100